



PG HD LEED Heat Transfer Fluid Technical Data Sheet

Product Overview

A fully formulated virgin bio-based propylene glycol heat transfer fluid containing a specially designed inhibitor package that controls the corrosion of metals; helps prevent scaling and the fouling of heat transfer surfaces and buffers the pH to maintain it in the optimum operating range. Used for heavy-duty applications, **SOLUTHERM™ PG HD LEED** has a recommended operating temperature range of -50°F to 325°F when mixed with appropriate water concentrations. It provides both freeze and burst protection for systems exposed to very low temperatures.

Product Technical Information

SOLUTHERM™ PG HD LEED inhibited virgin bio-based propylene glycol heat transfer fluid is manufactured with the highest quality raw materials. Each fluid is specially formulated with state-of-the-art inhibitor chemistry that prevents corrosion, which minimizes fluid expense and extends fluid life. **SOLUTHERM™** fluid is silicate-free and meets ASTM standard for corrosion protection and bio-based content; and is available in dilutions ranging from 30% to 70% PG. Please note that we recommend diluting only with RO (reverse osmosis) or distilled water to maintain corrosion protection.

Performance, Features and Benefits

- Fluid is dyed blue green for leak detection purposes
- Silicate free
- Meets the Heat Transfer Fluid ASTM D8039 standard for multi-metal corrosion protection and foaming tendency for ready-to-use heat transfer fluids when a minimum of 30% is used
- Available in dilutions ranging from 30% to 70%
- Significant reduction in GHG
- Potential LEED innovation credits
- Renewable sustainable bio-based product
- Operating temperature of -50°F to 325°F



RECOCHEM INC.
SECURING YOUR JOURNEY
RECOCHEM.COM



CONTACT US:
CUSTOMERSERVICE@RECOCHEM.COM
1-800-361-6030

Product Use

SOLUTHERM™ PG HD LEED is intended for use in heavy-duty processing applications where a bio-based glycol coolant is required. Before initial fill with **PG HD LEED**, the system should be prepared by an appropriate flushing procedure followed by complete removal of flushing fluid.

Once filled, it is natural for **PG HD LEED** thermal management fluid inhibitor levels to slowly depreciate over time. The fluid may be maintained in the system for up to 10 years with proper fluid monitoring and addition of recommended boosters and treat rates provided by our fluid analysis program.

Storage and Disposal

Store **SOLUTHERM™ PG HD LEED** in original container in a cool, dry environment away from direct sunlight. When properly stored, the product is suitable for use for up to 2 years after manufacture. Do not use galvanized steel for storage or handling systems. Refer to SDS for product safety information. Discard unused or end of life product in accordance with local, regional, or national regulations.

Specifications:

The corrosion inhibitor package in **SOLUTHERM™ PG HD LEED** Heat Transfer Fluid is designed to meet and exceed the following Classification and Specifications:

- ASTM D8039
- ASTM D6866
- USDA BioPreferred®

PRODUCT OFFERING INCLUDES:

TYPICAL PROPERTIES	SOLUTHERM™ PG HD LEED Concentrate	SOLUTHERM™ PG HD LEED 70	SOLUTHERM™ PG HD LEED 60	SOLUTHERM™ PG HD LEED 50	SOLUTHERM™ PG HD LEED 40	SOLUTHERM™ PG HD LEED 30
Propylene Glycol % Weight	95%	70%	60%	50%	40%	30%
Corrosion Inhibitors and Water % Weight	5%	30%	40%	50%	60%	70%
Color	Blue Green					
ASTM Specification	D8039					
pH of Solution	Depending on Dilution	9.2-10.6	9.2-10.6	9.2-10.6	9.2-10.6	9.2-10.6
Reserve Alkalinity, mL	14.3 min	10.3 min	8.9 min	7.4 min	5.9 min	4.5 min
Pounds per Gallon (68°F)	8.80	8.82	8.80	8.75	8.69	8.60
Boiling Point	Depending on Dilution	230°F (110°C)	225°F (107°C)	222°F (106°C)	219°F (104°C)	216°F (102°C)
Freezing Point	Depending on Dilution	Below -60°F (-51.1°C)	<-60°F (<-51.1°C)	-28°F (-33.6°C)	-7°F (-21.4°C)	9°F (-13.0°C)



Find out more ►
www.solutherm.com



RECOCHEM INC.
SECURING YOUR JOURNEY
RECOCHEM.COM



CONTACT US:
CUSTOMERSERVICE@RECOCHEM.COM
1-800-361-6030